

DRT-15CE PORTABLE TURBIDIMETER

laboratory accuracy in a rugged , portable package



DRT-15CE PORTABLE TURBIDIMETER

Standard Features:

- ▶ **Rugged Portable Carrying Case**
Ensures durability and convenience no matter where your laboratory happens to be.
- ▶ **Completely Self-Contained**
Provides easy access to everything you need to take a measurement.
- ▶ **Three User Selectable Ranges**
Provides accuracy in a wide variety of applications from 0 to 1000 NTU.
- ▶ **20 Hour Rechargeable Battery**
Always be ready to go with up to 20 hours of continuous operation when fully charged.

Optional Features:

- ▶ **Automobile Adapter**
Charge and operate the DRT-15CE from the cigarette lighter in your automobile.
- ▶ **PrimeTime Calibration Standards**
Quick and easy calibration across all ranges without the need to mix Formazin.
- ▶ **Formazin Stock Solution Kit**
Contains everything you need to calibrate the DRT-15CE with Formazin, the primary calibration standard.

Designed to provide the rugged portability needed in the field with the accuracy demanded in the laboratory, the EPA approved* DRT-15CE has become a “must have” for anyone monitoring turbidity on the go. The integral carrying case holds everything needed for field operation. With resolution of 0.01 NTU and an extended range to 1,000 NTU, the DRT-15CE is a perfect fit for both field and laboratory use.

* The DRT-15CE exceeds performance criteria specified by US EPA method 180.1 for NTU measurement.

Specifications

Range:	0 - 10 NTU 0 - 100 NTU 0 - 1000 NTU
Accuracy:	0-10 NTU, $\pm 1\%$ of full scale 0-100 NTU, $\pm 5\%$ of full scale 0-1000 NTU, $\pm 10\%$ of full scale
Resolution:	0.1% of selected range
Response Time:	Immediate
Sample Size:	25 ml (16 ml minimum)
Operating Temperature:	32° - 122°F (0° - 50°C)
Battery:	6V gel-cell rechargeable with 20 hours of continuous use when fully charged.
Recharge Time:	8 hours to full charge
Dimensions:	11 x 8 x 5 - inches (28 x 20 x 14 cm)
Weight:	5 lbs (2.27 kg)
Standards Compliance:	USEPA, CE Approved

ORDERING INFORMATION

Catalog No.	Description
19057	DRT-15CE Portable Turbidimeter, 120 VAC
19058	DRT-15CE Portable Turbidimeter, 240 VAC

The DRT-15CE includes one 0.02 NTU reference standard, one measuring cuvette with light shield cap, operators manual and a dual purpose adapter charger.

Accessories

19045	12V Automobile Adapter: to operate & charge the DRT-15CE from a cigarette lighter plug.
29071	PrimeTime Calibration Kit (0.02, 10.00, 100.0 & 1000 NTU).
50051	Cuvettes, 28 x 70 mm, 3 pack
50052	Cuvettes, 28 x 70 mm, 10 pack

Represented by:

 **scientific, inc.**
3170 Metro Parkway
Ft. Myers, FL 33916-7597
Phone: (239) 337-2116
Fax: (239) 332-7643
Email: info@hfscientific.com
<http://www.hfscientific.com>

Revised 04/29/03