

Real-time ambient dust monitor  
designed for continuous monitoring

Product Specifications

## Thermo Scientific ADR-1500 Area Dust Monitor



### Key Features

- Volumetric flow control
- Modular optics and long-life primary HEPA filter for simple servicing
- Multiple power and communications capabilities
- Durable weather-proof IP65 enclosure
- Designed for ease of transport and installation

The Thermo Scientific ADR-1500 Area Dust Monitor utilizes highly sensitive light-scattering photometer (nephelometer) technology, as used in the Thermo Scientific pDR Series monitors. The intensity of light scattered by airborne particles passing through the sensing chamber is linearly proportional to their concentration. This optical configuration produces optimal response to particles providing continuous measurements of the concentrations of airborne particles for total particulate and cut-points ranging from PM-10 down to PM-1.

The ADR-1500 monitor incorporates a temperature and relative humidity (RH) sensor coupled with an internal heater to mitigate the positive bias with elevated ambient RH. Additionally, the flow control is truly volumetric and is maintained through digital feedback of the onboard barometric pressure sensor, temperature sensor, and calibrated differential pressure across a precision

orifice. The principles of true volumetric flow, as incorporated by the ADR-1500 monitor, result in an accurate sample volume and precise particle cut-point.

The measured concentration of particulate matter is displayed in real-time on the two-line LCD readout display. Additional values can be displayed, such as run start time and date, time averaged concentrations, elapsed run time and many more.

The flexible power capabilities allow the ADR-1500 monitor to operate on AC, external DC, or an internal battery. Communications options are available for USB, RS-232, analog and wireless capability.

The ADR-1500 monitor is housed in a weather-proof IP65 enclosure producing a compact and durable instrument that is ready for rapid deployment and unattended operation.

## Product Specifications

To maintain optimal product performance, you need immediate access to experts worldwide, as well as priority status when your air quality equipment needs repair or replacement. We offer comprehensive, flexible support solutions for all phases of the product life cycle. Through predictable, fixed-cost pricing, our services help protect the return on investment and total cost of ownership of your Thermo Scientific air quality products.

### Thermo Scientific ADR-1500 Area Dust Monitor

<b>Concentration Measurement Range</b>	0.001 to 400 mg/m <sup>3</sup> (auto-ranging)
<b>Scattering Coefficient Range</b>	1.1 x 10 <sup>-6</sup> to 0.6m <sup>-1</sup> (approximately) @ λ = 880nm
<b>Precision / Repeatability</b>	+/- 2% of reading or +/- 0.005 mg/m <sup>3</sup> , whichever is larger, for 1-second averaging time
<i>2-sigma<sup>2</sup> with heater off and</i>	+/-0.5% of reading or +/- 0.0015 mg/m <sup>3</sup> , whichever is larger, for 10-second averaging time
<i>RH correction disabled (over 30 days)</i>	+/-0.2% of reading or +/- 0.0005 mg/m <sup>3</sup> , whichever is larger, for 60-second averaging time
<b>Accuracy</b>	+/- 5% of reading (+/- precision) traceable to SAE Fine test dust
<b>Resolution</b>	0.1 µg/m <sup>3</sup>
<b>Particle Size Range of maximum response</b>	0.1 to 10 µm
<b>Flow Rate Range</b>	1.0 to 3.5 liters/min.
<b>Aerodynamic Particle Cut-Point Range</b>	1.0 to 10 µm, with optional cyclone accessories
<b>Alarm Averaging Time</b>	Real-time (1 - 60 seconds) or STEL (15 minutes)
<b>Data Logging Averaging Periods</b>	1 second to 1 hour
<b>Logged Data</b>	Averaged concentrations, temperature, RH, barometric pressure, time/date, and data point number
<b>Run Summary</b>	Site number, average and max. concentrations, time/date of maximum, number of logged points, start time/date, elapsed time (run duration), averaging (logging) period, calibration factor and tag number
<b>Serial Interface</b>	High speed, USB/RS-232 (reserved for wireless applications), 19,200 baud
<b>Real-Time Digital Signal</b>	Concentration, flow, temperature, relative humidity, barometric pressure, time, date
<b>Real-Time Analog Signal</b>	0 to 2 V and 4 to 20 mA, with selectable full scale ranges between 0.1 and 400 mg/m <sup>3</sup> 0-0.1, 0-0.4, 0-1.0, 0-4.0, 0-10, 0-40, 0-100 and 0-400, mg/m <sup>3</sup>
<b>Alarm Output</b>	Load impedance > 100 kΩ, Alarm ON = short to ground, Alarm OFF = open
<b>Internal Battery Run Time</b>	1.2 L/min. (heater and alarm constantly on) > 24-hour run time
<b>AC Source</b>	100-240 VAC, 50/60Hz, 12/24 Vdc for solar or auxiliary battery options
<b>Operating Environment</b>	14 to 122°F (10 to 50°C) 10 to 95% RH, non-condensing
<b>Physical Dimensions</b>	21" (533mm) H x 17" (431mm) W x 17" (215mm) D, 28.5 lbs. (12.9 kg)
<b>Optional Cyclones</b>	GK 2.05 (Red) primarily for PM-4 through PM-10, SCC 1.062 (blue) for PM-1 through PM-4

### Ordering Information

#### ADR-1500 Area Dust Monitor

Choose from the following configurations/options to customize your own ADR-1500 monitor

#### 1. Power cords:

A = 110v power cord  
B = 220v power cord

#### 2. Relay kit:

A = Relay kit  
N = No relay kit

#### 3. Pole mounting:

A = Pole mount kit, 2" DIA  
B = Pole mount kit, 3" DIA  
C = Pole mount kit, 4" DIA  
N = None

#### 4. External cables:

A = Analog external cable assembly  
B = 12/24 Vdc external cable assembly  
C = Both cables  
N = None

#### 5. 37mm Cassette filter holder assembly

A = 37mm Cassette filter holder assembly with filter support & holder  
N = None

#### 6. Cyclone and the cyclone adapter

A = Blue cyclone assembly (PM 1 - 2.5 Microgram CP) with cyclone adapter  
B = Red cyclone assembly (PM 4 - 10 Microgram CP) with cyclone adapter  
C = Both cyclones with cyclone adapter  
N = None

**Your Order Code: ADR1500-** \_\_\_\_\_

Lit\_ADR1500AQL\_11/10

© 2010 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries.

This specification sheet is for informational purposes only and is subject to change without notice. Thermo Fisher Scientific makes no warranties, expressed or implied, in this product summary. Not all products are available in all countries. Please consult your local sales representative for details.

This product is manufactured in a plant whose quality management system is ISO 9001 certified.

#### Air Quality Instruments

27 Forge Parkway  
Franklin, MA 02038 USA

(866) 282-0430  
(508) 520-0430  
(508) 520-1460 fax

[www.thermoscientific.com/AQL](http://www.thermoscientific.com/AQL)

**Thermo**  
SCIENTIFIC